



RELIABLE, EFFICIENT AND

GOOD LOOKING



2 DOOR CHILLER



Model No:	IC2C
Dimension in mm (W*D*H)	620*760*1955
Capacity in Ltrs	500
Temperature	2 Deg C
Doors	2
No of Shelves	3
Refrigerant	R134a
Compressor	Aspera
Cooling Type	Ventilated
Insulation Type	Polyurethane
Temperature Controller	Carel, Italy
Voltage	230V, 50 Hz
Weight in Kgs	105

4 DOOR CHILLER

Model No	IC4C
Dimension in mm (W*D*H)	1220*760*1955
Capacity in Ltrs	1000
Temperature	2 Deg C
Doors	4
No of Shelves	6
Refrigerant	R134a
Compressor	Aspera
Cooling Type	Ventilated
Insulation Type	Polyurethane
Temperature Controller	Carel, Italy
Voltage	230V, 50 Hz
Weight in Kgs	177



2 DOOR FREEZER



Model No:	IC2F
Dimension in mm (W*D*H)	620*760*1955
Capacity in Ltrs	500
Temperature	Minus 18 Deg C
Doors	2
No of Shelves	3
Refrigerant	R404a
Compressor	Aspera
Cooling Type	Ventilated
Insulation Type	Polyurethane
Temperature Controller	Carel, Italy
Voltage	230V, 50 Hz
Weight in Kgs	105

FEATURES BENEFITS

- ▶ Constructed out of Food Grade Stainless Steel
- ▶ Aspera / Embraco Compressor
- ▶ Safe Food
- ▶ Low Power Consumption
- ▶ Replaceable Door gasket
- ▶ Adjustable Shelf
- ▶ Auto Defrost
- ▶ Easy Cleaning
- ▶ Flexible Storage option
- ▶ No Drains required

4 DOOR FREEZER

Model No	IC4F
Dimension in mm (W*D*H)	1220*760*1955
Capacity in Ltrs	1000
Temperature	Minus 18 Deg C
Doors	4
No of Shelves	6
Refrigerant	R404a
Compressor	Aspera
Cooling Type	Ventilated
Insulation Type	Polyurethane
Temperature Controller	Carel, Italy
Voltage	230V, 50 Hz
Weight in Kgs	177



2 DOOR UNDER COUNTER CHILLER



Model No	2UCC
Dimension in mm (W*D*H)	1400*700*850
Capacity in Ltrs	320
Temperature	2 Deg C
Doors	2
No of Shelves	2
Refrigerant	R134a
Compressor	Danfoss
Cooling Type	Ventilated
Insulation Type	Polyurethane
Temperature Controller	Carel, Italy
Voltage	230V, 50 Hz
Weight in Kgs	105

3 DOOR UNDER COUNTER CHILLER

Model No	3UCC
Dimension in mm (W*D*H)	1875*700*850
Capacity in Ltrs	500
Temperature	2 Deg C
Doors	3
No of Shelves	3
Refrigerant	R134a
Compressor	Danfoss
Cooling Type	Ventilated
Insulation Type	Polyurethane
Temperature Controller	Carel, Italy
Voltage	230V, 50 Hz
Weight in Kgs	135



*All specifications are subject to change w/o prior notice of continuous improvement

▶ Carel / Dixel Controller
Easy Operation

▶ Ventilated Cooling
Uniform Cooling

▶ 60mm, 40kg/m3 Insulation
Better Performance

▶ Flexible Wheels
Easy to Clean Floor Area

▶ Round Corners
Easy to clean the unit

▶ Self Closing Door
Time Saved on Productive work

VERTICAL DISPLAY CHILLER



PRODUCT SPECIFICATIONS

Model	Vertical Display Chiller
Model #	VDC4
Dimension in mm (W*D*H)	1280*820*2065
Capacity in Ltrs	1000
Temperature	0 Deg C
Doors	4
No of Shelves	6
Refrigerant	R134a
Compressor	Embraco
Cooling Type	Ventilated
Insulation Type	Polyurethane
Temperature Controller	Dixel
Voltage	230V, 50 Hz
Weight in Kgs	130



INDICOOL INNOVATIONS PVT.LTD.

HEAD OFFICE

#12, Shakthi Nagar, Mount Poonamallee Road,
Porur, Chennai-600116

Contact Person:

Mr. Mano Krishnamoorthy
krishna@theindicool.com
Mobile: +91 98402 87878

KARNATAKA OFFICE

#272, GEF Post Office, Mysore Road
Near Telephone Exchange, Bangalore 560026

Contact Person:

Mr. Chandra Mouli
chandramouli@theindicool.com
Mobile: +91 98802 02939

ANDHRA OFFICE

Sri Sai Nilayam, Pichireddy Thopu Veedi
Near Ex MLA Mr. Nelavala Subramanyam's House
Naidupet, Nellore District, Andhra Pradesh - 524126
chandramouli@theindicool.com

DEALER OFFICE